




**GEOTECHNICAL INVESTIGATION REPORT
FOR NOTICE OF REQUIREMENT APPLICATION**

Waitākere District Courthouse

**14 Edmonton Road
Henderson, Auckland**

Prepared by:



Prepared for:

MINISTRY OF JUSTICE

Justice Centre
19 Aitken Street
Wellington

04 April 2025

Project Number: 1496-01-24

COMMERCIAL IN CONFIDENCE

TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
1.1	PROJECT DESCRIPTION.....	1
1.2	PURPOSE OF INVESTIGATION.....	2
2.0	INVESTIGATIONS.....	3
2.1	DESKTOP STUDY	3
2.2	FIELD INVESTIGATIONS	3
3.0	SITE AND GROUND CONDITIONS	4
3.1	SITE CONDITIONS.....	4
3.2	SUBSURFACE CONDITIONS	4
3.2.1	Geology.....	4
3.2.2	Generalised Ground Conditions.....	4
3.2.3	Groundwater	5
4.0	GEOLOGIC AND SEISMIC HAZARDS	6
4.1	LANDSLIDING, EROSION, SUBSIDENCE.....	6
4.2	FALLING DEBRIS	6
4.3	SURFACE FAULT RUPTURE	6
4.5	LIQUEFACTION	6
4.6	LATERAL SPREADING.....	6
4.7	HIGHLY COMPRESSIBLE SOILS	7
4.8	EXPANSIVE SOILS	7
4.9	FLOODING	7
4.10	TSUNAMI	8
4.11	VOLCANIC ERUPTION	8
4.12	COASTAL INUNDATION.....	8
4.13	ENVIRONMENTAL ISSUES.....	8
5.0	CONCLUSIONS AND RECOMMENDATIONS.....	9
5.1	GEOTECHNICAL CONSTRAINTS	9
5.2	SITE SUBSOIL CLASS	9
5.3	FOUNDATION SUPPORT	9
5.4	EARTHWORK CONSIDERATIONS	9
5.5	FURTHER WORK	10
6.0	APPLICABILITY AND LIMITATIONS.....	11
7.0	REFERENCES.....	12
APPENDIX A – PLATES		
APPENDIX B – CONCEPT DESIGN SITE PLAN		
APPENDIX C – LOGS OF DEEP SITE INVESTIGATIONS		
APPENDIX D – LOGS OF SHALLOW SITE INVESTIGATIONS		

1.0**INTRODUCTION**

This report has been prepared to support a Substantive Application made by Ministry of Justice (on behalf of the Requiring Authority - Minister of Justice) under the Fast Track Approval Acts 2024 in accordance with the requirements of Section 42. The proposal is a Referred Project and this report has been prepared to support a Notice of Requirement Application to designate the site at 14 Edmonton Road, Henderson for 'Judicial and Court purposes' known as the Waitakere District Courthouse - New Courthouse project. Under s42(4)(d), this substantive application is giving notice of a requirement to designate the site that would otherwise be applied for under the Resource Management Act 1991. Section 43 of the Fast Track Approval Act sets out the information to be included in a substantive application, which includes an assessment of adverse effects of the project on the environment. This report has been prepared to assess the potential geotechnical hazard risks of the project, and presents the findings, conclusions and recommendations from Wentz-Pacific Ltd's (WP's) geotechnical investigation of the site.

The work described herein was commissioned by the Ministry of Justice (MoJ) and was completed in general accordance with WP's agreement with MoJ dated 21 August 2024.

1.1 PROJECT DESCRIPTION

The MoJ has purchased the site located at 14 Edmonton Road in the Henderson suburb of Auckland (refer to Plate A-1, Appendix A) in anticipation of building a new 'Justice Facility'. Given the proposal is for Notice of Requirement Application and the development proposal for a future building is not confirmed or known, the investigation and assessment provided in this report is based on the concept development scheme for a future building envelope.

In particular, this includes a six-storey courthouse with 10 courtrooms, four hearing rooms and associated spaces. [REDACTED] and no basement or below ground parking is proposed. The indicative gross floor area (GFA) for the building is circa 12,000 m², and the ground floor structure footprint (including parking) will encompass circa 3,000 m². No major earthworks are anticipated to support the construction of a future building on the site.

WP's understanding of the project is based on our discussions with [REDACTED] and on our review of Concept Design drawings by Architectus. The indicative building footprint on the site is shown on the concept design landscape plan dated April 2025 by Architectus (refer Appendix B).

1.2 PURPOSE OF INVESTIGATION

The purpose of WP's geotechnical site investigation was to:

- characterise (from a geotechnical standpoint) the ground and groundwater conditions across the site;
- identify potential geotechnical hazards / constraints that may impact development; and,
- provide high-level comment on geotechnical recommendations / mitigation measures that are likely to be required for building foundation support or to address identified geotechnical constraints.

2.0 INVESTIGATIONS

2.1 DESKTOP STUDY

A review of select and available information pertaining to the site and/or surrounding vicinity was conducted. Specifically, this information included:

- Aerial photographs contained on the Auckland Council (AC) and Retrolens websites.
- Natural hazard information contained on the AC website.
- Regional geological information published by the Institute of Geological & Nuclear Sciences Limited (GNS).
- Data from several shallow geotechnical investigations undertaken across the site by others and provided to WP by the MoJ.
- Data from various deep geotechnical investigations undertaken in the general vicinity of the site obtained from the NZ Geotechnical Database.

2.2 FIELD INVESTIGATIONS

Deep Investigations

Four cone penetrometer tests (CPTs) were performed at the site on 03 September 2024 at the approximate locations shown in Plate A-2 in Appendix A. The CPTs were advanced to depths of between about 6.7 and 13.4 m below existing ground (bgl). All of CPT soundings were pushed into the inferred top of the East Coast Bays geologic formation where practical refusal was encountered. The CPT investigation results are presented in Appendix C.

Two machine (deep) boreholes were drilled at the site on 03 September 2024 at the approximate locations shown in Plate A-2 in Appendix A. The boreholes were drilled to depths of 10.7 and 13.7 m bgl and terminated in confirmed East Coast Bays Formation rock.

A 3 m deep standpipe piezometer was installed in MH01 to allow periodic measurement of shallow groundwater at this location. The logs of the boreholes are presented in Appendix C.

Previous Shallow Investigations

A previous geotechnical investigation by Soil & Rock Consultants (2023) included five hand auger boreholes across the site to depths of 3 to 5 m bgl. The boreholes were drilled in 2018 and inferred to have been done as part of the investigation of a larger development. Dynamic cone penetrometer (DCP) testing was carried out of the base of the boreholes to depths of 3.9 to 6.8 m bgl where practical test refusal was encountered. The locations of the previous investigations are shown on Plate A-2 in Appendix A, and the logs of the boreholes and DCP tests are contained in Appendix D.

3.0**SITE AND GROUND CONDITIONS**

3.1 SITE CONDITIONS

The roughly rectangular-shaped and flat-lying site encompasses 4435 m². The majority of the site is paved car parking, and part of the parking appears to be used for a bicycle track. A few established trees occupy parts of the perimeter of the site.

The site is bordered the north by the Oratia stream, the Alderman restaurant and Falls Park. Alderman Drive and Edmonton Road run along the west and south sides of the site, respectively. To the east, the site is bounded by the driveway into the Korean Presbyterian Church and primary residential properties beyond.

3.2 SUBSURFACE CONDITIONS**3.2.1 Geology**

Published geological information (Edbrooke, 2001) shows the site to be surfaced with late Pliocene to middle Pleistocene-age alluvial sediments of the Puketoka Formation (Pup). These sediments are described as “pumiceous mud, sand and gravel with muddy peat and lignite: rhyolite pumice, including non-welded ignimbrite, tephra and alluvial deposits; massive micaceous sand”. This formation is known to contain significant deposits of estuarine peat and organic soils – including fibrous root masses and timber – as well as methane and hydrogen sulphide gas accumulations (Boyd and Macklin, 2017).

The deep investigations confirmed that the Pup sediments are underlain by residual soil and sedimentary rock of the Miocene-age East Coast Bays Formation (Mwe). This formation is described by Edbrooke (2001) as “alternating sandstone and mudstone with variable volcanic content and interbedded volcanoclastic grits”.

3.2.2 Generalised Ground Conditions

The two hand auger boreholes located in landscape / grass strips (AH09 and AH11) encountered about 200 to 600 mm of topsoil and / or undocumented fill. The three hand augers located in asphalt areas (AH10, -12 and -13) encountered gravel fill basecourse in the order of 300 to 350 mm thick directly beneath the asphalt.

The topsoil and fill were underlain by the alluvial soils of the Puketoka Formation extending to a depth of about 6 m bgl. These soils generally comprised of stiff to very stiff, low to moderate plasticity silt / clayey silt interbedded with occasional layers of soft to very stiff, highly plastic clay. Undrained shear strengths in these materials generally ranged from approximately 40 kPa to greater than 150 kPa.

A noticeably weaker layer of clayey material was noted between a depth of about 2.5 and 4 m in the hand auger boreholes located in the central and eastern part of the site. CPT-03, located in the southeastern part of the site, identified a layer of notably softer soil (undrained shear strengths between about 20-40 kPa) from a depth of about 2.5 to 5 m bgl.

DCP testing out of the base of the hand auger boreholes reached effective refusal (defined as a blowcount $\geq 20/100$ mm) at depths of 6.4 and 6.8 m in boreholes AH09 and AH10, and near refusal at depths of 3.9 to 5.9 m in AH11 through AH13.

The inferred depth to East Coast Bays formation (ECBF) residual soil based on the results of the CPT soundings ranges from approximately 5 to 6 m across the site, and this depth was confirmed in the machine boreholes.

The depth to slightly weathered ECBF rock was proven in the machine boreholes at a depth of about 12 m in BH01 in the northeastern corner of the site, and about 8 m in BH02 in the southwestern corner of the site.

3.2.3 Groundwater

Groundwater was measured (at the time of drilling) in three of the 2018 hand auger boreholes located in the central and eastern half of the site, at depths ranging from 0.8 m to 2.6 m. A 3 m deep piezometer was installed in borehole MH01, located in the northeast corner of the site relatively close to Oratia Stream.

The groundwater levels measured to date in the piezometer were:

- 05 September 2024: 2.4 m
- 12 September 2024: 2.3 m
- 19 September 2024: 2.0 m

Wet to saturated soils were logged in both of the deep boreholes at a depth of about 4 m.

The invert of the Oratia Stream north of the site boundary was visually estimated to be about 6 m lower than the car park where the piezometer is located. Topographic contour information on the Auckland Council website (AC Geomaps 2025) shows the invert to be about 5 m lower than the car park.

Based on the above information, it is inferred that there is a perched water layer across the site at a depth of around 2 m, and possibly shallower in some areas, but that the “permanent” groundwater level is deeper – around 4 m (i.e., closer to the level of the nearby Oratia Stream). This will need to be confirmed by further measurements and possibly installation of a second piezometer should the depth to groundwater be required for design and / or construction.

Groundwater levels at the site may fluctuate over time from those reported herein due to variations in rainfall, irrigation practices (both on- and off-site), runoff conditions, tidal fluctuations in the nearby estuary, and other factors.

4.0**GEOLOGIC, SEISMIC AND OTHER HAZARDS**

4.1 LANDSLIDING, EROSION, SUBSIDENCE

The site is essentially level and not bordered by steeply sloping terrain or ground that otherwise appears to be potentially unstable or prone to slippage. At the time of our site investigation, no evidence of significant erosion or ground subsidence was observed – including along Oratia stream near the northern site boundary. The risk of slope instability to the site is considered to be very low.

4.2 FALLING DEBRIS

There are no uphill sources of debris that can impact this site.

4.3 SURFACE FAULT RUPTURE

The Active Faults Database (2025) does not show any active faults (generally defined as faults which have deformed the ground surface within the past 125,000 years) running through, or close to the site.

4.5 LIQUEFACTION

Based on the results of our site-specific deep investigations, the site soils are not considered susceptible to liquefaction due to:

- the cohesive and / or cemented nature of the fine-grained soils; and,
- the dense to very dense state of the coarse-grained soils.

WP considers the liquefaction hazard at the site to be very low, and no specific liquefaction mitigation measures are considered necessary for the proposed development.

4.6 LATERAL SPREADING

Lateral spreading occurs during or shortly after an earthquake when liquefied soil moves laterally toward a free face (e.g., stream bank or slope of an open channel), or when a non-liquefied “crust” moves laterally toward a free face on an underlying layer of liquefied soil. The greatest displacements typically occur near to the free face and gradually reduce with increasing distance from the free face.

While there is an approximately 5 to 6 high slope of the Oratia streambank located within about 20 m of part of the northern site boundary, the probability of the site being affected by lateral spreading during either a SLS or ULS event is considered to be very low because the site soils are not considered susceptible to liquefaction.

4.7 HIGHLY COMPRESSIBLE SOILS

The alluvial Puketoka Formation soils at the site vary in strength and stiffness both vertically and horizontally across the site. However, the site investigations to date have not identified any peat, highly organic, or otherwise very weak and/or compressible soils.

4.8 EXPANSIVE SOILS

Expansive soils are defined as soils that undergo large volume changes (shrink or swell) due to variations in soil moisture content. Such volume changes may cause damaging settlement and/or heave of foundations, slabs-on-grade, pavements, etc.

The near-surface soils found in the hand auger holes are generally characterised as having slight to moderate plasticity, but some highly plastic clayey soils were found at a depth of around 1 m. In the absence of site-specific laboratory testing to confirm otherwise, the shallow soils should be assumed to be 'Site Class H – Highly Expansive' as described in B1/AS1 or 'H1' as per AS 2870:2011.

4.9 FLOODING

The small portion of the northern part of the site is shown to be located within an Auckland Council-identified 'flood plain' area (AC Geomaps, 2025) – indicating that it is predicted to be covered by water as a result of a 1 in 100-year flood as shown in Figure 4-1. An overland flow path identified as draining an area of between 3 ha and 100 ha is also shown to run through the central portion of the site in a southerly direction. WP understands that site-specific flood modelling of the site is being undertaken by others and the AC flood information is shown for information only.



Figure 4-1 – Flood Plain (a); Overland flow paths (b)

4.10 TSUNAMI

The site is not shown as located within ‘Tsunami Evacuation Zone’ (AC Hazard Viewer, 2025). A ‘Yellow’ Evacuation Zone, indicating an area that would need to be evacuated only in the event of a ‘maximum-impact’ tsunami, is located along the margins of Oratia Stream west of the site across Alderman Drive.

4.11 VOLCANIC ERUPTION

This site is not located within the Auckland Volcanic Field (AC Hazard Viewer, 2025).

4.12 COASTAL INUNDATION

The site is not located within an Auckland Council coastal inundation zone (AC Hazard Viewer, 2025).

4.13 ENVIRONMENTAL ISSUES

Environmental site assessment / engineering is beyond WP’s scope of work, and we recommend that an environmental specialist be engaged to assess this aspect of the site.

5.0**CONCLUSIONS AND RECOMMENDATIONS**

Based on the results of our site investigations and geotechnical assessment, WP makes the following conclusions and preliminary recommendations for foundation support.

5.1 GEOTECHNICAL CONSTRAINTS

No significant geotechnical risks or constraints have been identified on the site. The proposed six-storey structure will require deep foundations (e.g., bored concrete piles) extending into slightly weathered rock of the ECBF as discussed below.

5.2 SITE SUBSOIL CLASS

Based on the consistency and depth of soils found in WP's site investigation, and the depth to bedrock, WP recommends a site subsoil class of 'Class C – deep soil' as defined by NZS 1170.5 (2004) be used for seismic design.

5.3 FOUNDATION SUPPORT

The site soils overlying rock have variable strength and stiffness both vertically and horizontally. A relatively stiff crust in the order of 2 to 3 m thick is present across the site, and this layer is anticipated to be suitable for shallow foundation support of relatively light structures up to 2-storeys. However, heavier structures will need to be supported on deep pile foundations that extend into slightly weathered ECBF rock.

The depth to the top of a suitable founding layer for end-bearing bored concrete or similar piles is anticipated to range from about 8 m in the western part of the site to about 13 m in the eastern part, and possibly somewhat shallower in the central part of the site.

It is anticipated that an ultimate geotechnical strength of 6 MPa will be available for end-bearing piles with the base founded a minimum of three pile diameters into intact, slightly weathered ECBF rock (defined as a rock mass with three consecutive SPT N-values of not less than 50 over 3 m depth interval).

The soils supporting shallow foundation beams should be assumed to be highly reactive / expansive (i.e., Site Class H – Highly Expansive in B1/AS1 or H1 in AS 2870:2011) for conceptual design. The reactivity class should be confirmed with appropriate laboratory testing for later stages of design.

5.4 EARTHWORK CONSIDERATIONS

WP understands that no major earthworks will be required for the proposed development of the site. Based on the information from the 2018 Soil & Rock Consultants shallow investigations, it should be assumed that up to about 0.4 m of topsoil and/or undocumented fill may need to be removed from portions of the site depending on the extent of the developed area. The potential for areas of deeper or more extensive undocumented fill to exist that would

require removal cannot be precluded; however, extensive fill removal is considered unlikely based on the site investigations to date.

Site earthworks are not anticipated to extend to the perched or permanent ground water tables (depth of about 2 to 2.5 m), hence dewatering of excavations is not anticipated.

5.5 FURTHER WORK

Further work will be required to confirm the foundation conditions and geotechnical design criteria presented in this report. This work is expected to include:

- Additional machine-drilled boreholes within the final building footprint to confirm the depth to, and strength of the target rock bearing layer.
- Additional shallow hand auger investigations will also be required to confirm the near-surface ground conditions and obtain samples for laboratory testing to confirm the soil reactivity/expansivity.

A suitably qualified and experienced geotechnical engineer should be engaged for the duration of the project to design, monitor and certify the geotechnical aspects of the project.

Subject to the additional site investigations and future detailed design taking into account the ground conditions, conclusions and recommendations contained in this report, and the geotechnical aspects of the design being undertaken by a suitably qualified and experienced Chartered Professional Engineer, it is considered that potential adverse geotechnical hazard effects will be less than minor.

6.0**APPLICABILITY AND LIMITATIONS**

This report was prepared solely for the benefit of Ministry of Justice (the Client) and their project consultants with respect to the particular brief given to WP. The use by other parties of the information, opinions and recommendations contained in this report shall be at such parties' sole risk. This report is not intended to be used for design or building consent.

WP's services consist of professional opinions and conclusions developed in accordance with generally accepted geotechnical engineering principles and practices. There is no other warranty, either expressed or implied.

The opinions and recommendations in this report are based on subsurface information collected from discrete investigation / test locations, and the subsurface conditions away from these locations are inferred. It must be appreciated that the actual soil conditions could vary from those described in this report.

During site preparation and construction of bulk earthworks, the site should be examined by a geotechnical professional with the appropriate skills and experience to determine whether the exposed subsoils are compatible with the inferred conditions on which the recommendations in this report are based. If the ground conditions found at the site are found to differ from those described in this report, WP should be contacted immediately so that we can review our recommendations and if revise them if necessary.

7.0

REFERENCES

Auckland Council (2025). GeoMaps, viewed 02 April, <https://geomapspublic.aucklandcouncil.govt.nz/viewer/index.html>

Auckland Council (2025). Hazard Viewer, viewed 02 April, <https://aucklandcouncil.maps.arcgis.com/apps/MapSeries/index.html?appid=81aa3de13b114be9b529018ee3c649c8>

Boyd, ME and Macklin, SR (2017). The Puketoka Formation, Auckland New Zealand. A review of geotechnical properties and hazards for tunnelling. 16th Australasian Tunnelling Conference 2017: Challenging Underground Space: Bigger, Better, More. Barton, ACT: Engineers Australia. [94]-[103].

Edbrooke, S.W. (compiler) (2001). Geology of the Auckland area. Institute of Geological and Nuclear Sciences 1:250,000 geological map 3. 1 sheet + 74 p. Lower Hutt, Institute of Geological and Nuclear Sciences Limited.

New Zealand Active Faults Database (2025). GNS Science, viewed 02 April, <http://data.gns.cri.nz/af/index.html>

Soil & Rock Consultants (2023). Geotechnical Due-Diligence Investigation at 14 Edmonton Road, Henderson. Rev C. 13 February 2023.

APPENDIX A

PLATES





SOURCE: AUCKLAND COUNCIL GEOMATICS

SITE BOUNDARY

- APPROXIMATE LOCATION OF CPT (2024)
- APPROXIMATE LOCATION OF MACHINE BOREHOLE (2024)
- APPROXIMATE LOCATION OF HAND AUGER BOREHOLE (2018)



Client: Ministry of Justice
Waitakere District Courthouse
Project No.: 1496-01-24

Drawn by: DD
Reviewed by: RW
Date: April 2025

Site Investigation Plan
Waitakere District Courthouse
14 Edmont Road, Henderson, Auckland

PLATE
A-2


APPENDIX B

CONCEPT DESIGN SITE PLAN






1. Indicative Permeable Areas



2. Indicative Impermeable Areas



APPENDIX C

LOGS OF DEEP SITE INVESTIGATIONS





BOREHOLE LOG

Hole No.:

MH01

Client: Wentz-Pacific Ltd
Project: Geotechnical Investigation
Site Location: 14 Edmonton Road, Henderson

Contractor: Pro-Drill Ltd (Akl)
Rig: SLG
Driller: Clutch

Project ID: 27042
Start Date: 03/09/2024
End Date: 03/09/2024

Test Location: See plan
Located By: Site plan/map

Coordinates:
Elevation: Not set

Grid: NZTM
Datum: Ground

RL (m)	Geology	Material Description	Depth (m)	Graphic Log	In Situ Testing	Strength	Weathering	Defect Spacing	Defects and Drilling Remarks	Depth (m)	Drilling Method	TCR (%)	RQD (%)	Sampling	Water in/out flow	Backfill/ Installation/ Groundwater
-7	Puketokā	Sandy SILT, with minor clay; grey. Firm; wet; low plasticity.	6.5		SPT blows/75mm Shear vane peak/residual 31 / 15 kPa 0/0/1/1/1/3/4 N = 9					6.5	SPT	100				
-7		Clayey SILT, with trace sand; dark grey. Hard; moist; low plasticity; sand, fine.	7							7	Open Barrel	92				
-7		Silty SAND, with trace clay; dark grey. Dense; moist; non-plastic.	7.5							7.5						
-8			8		UTP 5/5/6/9/10/15 N = 40					8	SPT	0				
-8			8.5				EW	RS		8.5						
-8		8.50m: with very thin bed of carbonaceous material	9		7/7/11/8/9/10/15 N = 42					9	Triple tube	100				
-9	Weathered East Coast Bays Formation		9.5							9.5						
-9		Moderately weathered; dark grey; SILTSTONE; very weak.	10				VW	MW	9.60m: 4 Joints, Planar, 80°-90° Rough to 10m	10	Triple tube	100	63			
-10		Silty SAND; dark grey. Very dense; moist; non-plastic to weathered SANDSTONE; dark grey; Extremely weak.	10.5						9.95m: Parting, Planar, 70°-90° Rough	10.5						
-10			11		9/11/11/13/15/20 for 10mm N = 50+		EW	CW	10.20m: 3 Joints, Planar, 80°-90° Rough to 10.5m	11	SPT	100	0			
-11		Moderately weathered; dark grey; SILTSTONE; very weak.	11.5							11.5						
-11		11.20m: with thin bed very dense silty Sand to extremely weak SANDSTONE,	12							12						
-11		Slightly weathered; dark grey; Fine to medium grained SANDSTONE; weak.	12.5				VW	MW	11.10m: 8 Joints, Planar, 80°-90° Rough to 12.0m	12.5	Triple tube	100	58			
-11			13				W	SW		13						

Remarks:	PIEZO	DATE	LEVEL	REMARK	Hole Depth:	Inclination:
	1	5/09/2024	2.40		13.65	90.00
					Logged By:	Checked By:
					MK	JL
					DRAFT	Sheet 2 of 3

Materials are described in general accordance with NZGS 'Field Description of Soil and Rock' (2005).



BOREHOLE LOG

Hole No.:	MH01
Project ID:	27042
Start Date:	03/09/2024
End Date:	03/09/2024
Grid:	NZTM
Datum:	Ground

Client:	Wentz-Pacific Ltd	Contractor:	Pro-Drill Ltd (Akl)
Project:	Geotechnical Investigation	Rig:	SLG
Site Location:	14 Edmonton Road, Henderson	Driller:	Clutch
Test Location:	See plan	Coordinates:	
Located By:	Site plan/map	Elevation:	Not set

RL (m)	Geology	Material Description	Depth (m)	Graphic Log	In Situ Testing	Strength	Weathering	Defect Spacing	Defects and Drilling Remarks	Depth (m)	Drilling Method	TCR (%)	RQD (%)	Sampling	Water in/out flow	Backfill/ Installation/ Groundwater
-13	Weathered East Coast Bays Formation	[CONT] Slightly weathered; dark grey; Fine to medium grained SANDSTONE; weak.			SPT blows/75mm Shear vane peak/residual 12/20/31/19 for 20mm N = 50+				12.35m: Joint, Planar, 70°, Rough		SPT	0	0			
						W	SW				Triple tube	60	60			
-13									13.20m: 1 Joint, Planar to curved, 70°, Rough							
-14		EOH: 13.65m			7/43 N = 50+						SPT	0	0			
-15																
-16																
-17																

Remarks:	PIEZO	DATE	LEVEL	REMARK	Hole Depth:	Inclination:
	1	5/09/2024	2.40		13.65	90.00
					Logged By:	Checked By:
					MK	JL
Materials are described in general accordance with NZGS 'Field Description of Soil and Rock' (2005).				DRAFT	Sheet 3 of 3	



0.00m - 5.50m



5.50m - 8.70m



8.70m - 13.65m



BOREHOLE LOG

Hole No.:	MH02
Project ID:	27042
Start Date:	03/09/2024
End Date:	03/09/2024
Grid:	NZTM
Datum:	Ground

Client:	Wentz-Pacific Ltd
Project:	Geotechnical Investigation
Site Location:	14 Edmonton Road, Henderson
Test Location:	See plan
Located By:	Site plan/map

Contractor:	Pro-Drill Ltd (Akl)
Rig:	SLG
Driller:	Clutch
Coordinates:	
Elevation:	Not set

RL (m)	Geology	Material Description	Depth (m)	Graphic Log	In Situ Testing	Strength	Weathering	Defect Spacing	Defects and Drilling Remarks	Depth (m)	Drilling Method	TCR (%)	RQD (%)	Sampling	Water in/out flow	Backfill/ Installation/ Groundwater
		Materials extracted by Hydro Excavation.			SPT blows/75mm Shear vane peak/residual											
-1		1.50m: with sandy fine to medium gravel									Hydrovac	0				
-2		Silty CLAY; orange and grey streaked light brown. Stiff; moist; high plasticity.			1/1/1/1/1/2 N = 4						SPT	100				
-3	Puketoka Formation	Silty CLAY; orange and grey mottled light brown. Stiff; moist; high plasticity; moderately sensitive.									Open Barrel	95				
-4		Sandy SILT, with trace clay; light brown mottled light grey/blue. Very loose; saturated; non-plastic; with trace fine gravel sized, rounded pumice and clay clasts.			89 / 37 kPa 0/0/1/0/0/0 N = 1						SPT	100				
-5		Silty CLAY, with minor sand; orange mottled grey. Stiff; moist to wet; medium plasticity; sand, fine.									Open Barrel	100				
-6		Silty fine to coarse SAND, with trace clay; dark grey. Loose; saturated; non-plastic; with trace fine gravel sized, rounded pumice and clay clasts .									Open Barrel	100				
-7		4.65m: with 20mm bed of limonite			46 / 15 kPa 3/4/7/8/10/12 N = 37						SPT	100				
-8	Weathered East Coast Bays Formation	Silty medium SAND; dark grey. Dense; moist; non-plastic; with coarse white sand sized clasts.									SPT	100				
-9		5.80m: becoming silty fine sand, with occasional carbonaceous laminae									Triple tube	62				

Remarks: Note: some gravel falling downhole over first run	PIEZO	DATE	LEVEL	REMARK	Hole Depth:	Inclination:
					10.65	90.00
					Logged By:	Checked By:
					MK	JL
					DRAFT	Sheet 1 of 2

Materials are described in general accordance with NZGS 'Field Description of Soil and Rock' (2005).



BOREHOLE LOG

Hole No.:

MH02

Client: Wentz-Pacific Ltd
Project: Geotechnical Investigation
Site Location: 14 Edmonton Road, Henderson
Test Location: See plan
Located By: Site plan/map

Contractor: Pro-Drill Ltd (Akl)
Rig: SLG
Driller: Clutch
Coordinates:
Elevation: Not set

Project ID: 27042
Start Date: 03/09/2024
End Date: 03/09/2024
Grid: NZTM
Datum: Ground

RL (m)	Geology	Material Description	Depth (m)	Graphic Log	In Situ Testing	Strength	Weathering	Defect Spacing	Defects and Drilling Remarks	Depth (m)	Drilling Method	TCR (%)	RQD (%)	Sampling	Water in/out flow	Backfill/ Installation/ Groundwater
	Weathered East Coast Bays Formation	[CONT] Silty medium SAND; dark grey. Dense; moist; non-plastic; with coarse white sand sized clasts.			SPT blows/75mm 1/2/6/7/12/15 N = 40	EW	RS				SPT	0				
-7		medium SAND, Dark grey, Dense, moist, non-plastic to Completely weathered; dark grey; medium SANDSTONE; extremely weak.							6.45m: 3 Joints, Planar, 80°-90° Rough to 6.80m							
			7			EW	CW		7.00m: Parting, Stepped, 30°, Rough	7	Triple tube	99	90			
					3/7/11/20/13 for 30mm N = 50+						SPT	0	0			
-8		Slightly weathered; dark grey; SANDSTONE; very weak.	8						8.10m: 4 Joints, Planar, 80°-90° Rough to 8.50m	8						
		8.20m: coarsing downwards to coarse SANDSTONE														
		8.50m: becoming fine SANDSTONE, with occasional carbonaceous laminae														
-9			9		9/29/38/12 for 25mm N = 50+	VW	SW		9.30m: 8 Joints, Planar, 90°, Smooth to 10m, generally along medium SANDSTONE beds to 10.0m	9	SPT	0	0			
		9.30m: with 75mm bed medium SANDSTONE														
		9.40m: with 30mm bed medium SANDSTONE														
		9.50m: with 75mm bed medium SANDSTONE														
-10		9.90m: with 50mm bed medium SANDSTONE	10								Triple tube	94	75			
		10.10m: with 30mm bed of medium SANDSTONE														
		10.30m: with 30mm bed of medium SANDSTONE														
		10.40m: with 30mm bed of medium SANDSTONE														
		EOH: 10.65m			9/41 for 70mm N = 50+						SPT	0	0			
			-11							-11						
Remarks: Note: some gravel falling downhole over first run					PIEZO	DATE	LEVEL	REMARK	Hole Depth: 10.65		Inclination: 90.00					
Materials are described in general accordance with NZGS 'Field Description of Soil and Rock' (2005).									Logged By: MK		Checked By: JL					
									DRAFT		Sheet 2 of 2					

Generated with CORE-GS by Gero - Machine Borehole Log v3 - 6/09/2024 2:39:54 pm



0.00m - 4.95m



4.95m - 9.25m



9.25m - 10.65m

Cone Ref: 71238



General Information

Project: 14 Edmonton Road, Henderson, Auckland
Contractor: Ground Investigation
WGS84 (deg): -36.877693, 174.63486499999996
Elevation (m): Unknown
Date:
Location: 14 Edmonton Road, Henderson, Auckland
Rig details: 22 Tonne MAN Truck
Location method: Handheld GPS
Elevation datum:
Start time:

Test Setup

Standard: ISO 22476-1:2012

Test type:
Pre-Drill (m): 0.20
Start length (m): 0
Cone ID: 71238
Cone type: 15cm2 Subtraction

Cone class:

Manufacturer:

Calibration date:

Cone area ratio: 0.75

Sleeve area ratio: 0

Sleeve offset: 0.09

Filter type: U2 Stainless steel

Saturation method: Vacuum pump

Rig setup variation:

Test Result

Termination reason: Danger of buckling rods

Termination depth: 9.56

Ground water level: 0.9

Water level origin: Estimated

Backfill:

Observations and materials encountered:

Deviations and interruptions:

Deviations:
Interruptions:

Corrections applied:

Test category:

Operator name:

Manager name:

Corrected cone resistance:

$$q_{t_c} = q_c + u_2 \cdot (1 - \beta)$$

Friction ratio:

$$R_f = \frac{f_c}{q_c} \cdot 100$$

Non-normalised soil behaviour type (SBT):

Calculated using q_{m0} and R_f for the Robertson's 2010 non-normalised CPT soil behaviour chart using zone equations defined by P.W. Mayne in "Evaluating effective stress parameters and undrained shear strength of soft-firm clays from CPT and DMT" 2016

Soil behaviour type index, (used for non-normalised SBT) :

$$I_c = ((3.47 - \log(q_c))^2 + (\log(R_f) + 1.22)^2)^{0.5}$$

Friction ratio:

$$F_r = \frac{f_c}{q_c - \sigma_{v0}} \cdot 100$$

Refined normalised cone resistance:

$$Q_{n0} = \frac{(q_c - \sigma_{v0}) / \sigma_{vm}}{(\sigma_{v0} / \sigma_{vm})^n} \text{ where } n = 0.381 \cdot I_c + 0.05 \cdot (\sigma_{v0} / \sigma_{vm}) - 0.05 \leq 1.0$$

Normalised soil behaviour type index:

$$I_{cn} = ((3.47 - \log(Q_{n0}))^2 + (\log(F_r) + 1.22)^2)^{0.5}$$

Normalised pore pressure:

$$B_p = \frac{\Delta U}{q_c - \sigma_{v0}}$$

Normalised soil behaviour type (SBTn):

Calculated using Q_{n0} and F_r for the Robertson's 2010 normalised CPT soil behaviour chart using zone equations defined by P.W. Mayne in "Evaluating effective stress parameters and undrained shear strength of soft-firm clays from CPT and DMT" 2016

Undrained shear strength (s_u):

$$s_u = \frac{q_c - \sigma_{v0}}{N_{sk}}$$

Relative density (D_r):

$$D_r = 100 \cdot \sqrt{\frac{Q_{n0}}{350}}$$

Friction angle (ϕ'):

$$\phi' = 17.60 + 11 \cdot \log(Q_{n0})$$

Small strain shear modulus (G_0):

$$G_0 = (q_c - \sigma_{v0}) \cdot (0.0188 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)})$$

Estimated shear wave velocity (V_s):

$$V_s = \sqrt{\frac{G_0}{\rho}} \text{ where } \rho = \frac{\gamma}{\gamma_w}$$

Constrained modulus (M):

$$M = \alpha_{df}(q_c - \sigma_{v0})$$

when $I_{cn} > 2.2$

$$\alpha_{df} = Q_c \text{ when } Q_c < 14$$

$$\alpha_{df} = 14 \text{ when } Q_c > 14$$

when $I_{cn} < 2.2$

$$\alpha_{df} = 0.0188 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)}$$

Youngs modulus (E_s):


$$E_s = (q_c - \sigma_{v0}) \cdot (0.015 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)})$$

Estimated SPT N_{60} :

$$N_{60} = \frac{q_c / P_a}{8.5 \cdot (1 - \frac{1}{10})}$$

Zero Readings

kPa	Initial zeros	Final zeros	Final difference	Clean zeros	Clean difference
Cone resistance	6,838.80	6,838.80	0	-	-
Sleeve friction	464.10	457.50	-6.52	-	-
Pore pressure	737.70	737.70	0	-	-



General Information

Project: 14 Edmonton Road, Henderson, Auckland
Contractor: Ground Investigation
WGS84 (deg): -36.877704, 174.6352519999998
Elevation (m): Unknown
Date:
Location: 14 Edmonton Road, Henderson, Auckland
Rig details: 22 Tonne MAN Truck
Location method: Handheld GPS
Elevation datum:
Start time:

Test Setup

Standard: ISO 22476-1:2012

Test type:
Pre-Drill (m): 1.30
Start length (m): 0
Cone ID: 71137
Cone type: 15cm2 Subtraction

Cone class:

Manufacturer:

Calibration date:

Cone area ratio: 0.75

Sleeve area ratio: 0

Sleeve offset: 0.09

Filter type: U2 Stainless steel

Saturation method: Vacuum pump

Rig setup variation:

Test Result

Termination reason: High friction resistance

Termination depth: 6.69

Ground water level: 1.1

Water level origin: Measured

Backfill:

Observations and materials encountered:

Deviations and interruptions:

Deviations:
Interruptions:

Corrections applied:


Test category:

Operator name

Manager name:

Zero Readings

kPa	Initial zeros	Final zeros	Final difference	Clean zeros	Clean difference
Cone resistance	6,308.10	6,332.50	24.36	-	-
Sleeve friction	449.10	447.00	-2.11	-	-
Pore pressure	705.10	705.10	0	-	-



General Information

Project: 14 Edmonton Road, Henderson, Auckland
Contractor: Ground Investigation
WGS84 (deg): -36.877441, 174.635551
Elevation (m): Unknown
Date:
Location: 14 Edmonton Road, Henderson, Auckland
Rig details: 22 Tonne MAN Truck
Location method: Handheld GPS
Elevation datum:
Start time:

Test Setup

Standard: ISO 22476-1:2012

Test type:
Pre-Drill (m): 0.00
Start length (m): 0
Cone ID: 71137
Cone type: 15cm2 Subtraction

Cone class:

Manufacturer:

Calibration date:

Cone area ratio: 0.75

Sleeve area ratio: 0

Sleeve offset: 0.09

Filter type: U2 Stainless steel

Saturation method: Vacuum pump

Rig setup variation:

Test Result

Termination reason: Danger of buckling rods

Termination depth: 11.83

Ground water level: 1

Water level origin: Estimated

Backfill:

Observations and materials encountered:

Deviations and interruptions:

Deviations:
Interruptions:

Corrections applied:

Test category:

Operator name:

Manager name:



Corrected cone resistance:

$q_c = q_{c'} + u_2 \cdot (1 - \beta)$

Friction ratio:

$R_f = \frac{f_s}{q_c} \cdot 100$

Non-normalised soil behaviour type (SBT):

Calculated using q_{un} and R_f for the Robertson's 2010 non-normalised CPT soil behaviour chart using zone equations defined by P.W. Mayne in "Evaluating effective stress parameters and undrained shear strength of soft-firm clays from CPT and DMT" 2016

Soil behaviour type index, (used for non-normalised SBT) :

$I_c = ((3.47 - \log(q_c))^2 + (\log(R_f) + 1.22))^0.5$

Friction ratio:

$F_r = \frac{f_s}{q_c - \sigma_{v0}} \cdot 100$

Refined normalised cone resistance:

$Q_{rn} = \frac{(q_c - \sigma_{v0}) / \sigma_{v0n}}{(\sigma_{v0} / \sigma_{v0n})^n}$ where $n = 0.381 \cdot I_c + 0.05 \cdot (\sigma_{v0} / \sigma_{v0n}) - 0.05 \leq 1.0$

Normalised soil behaviour type index:

$I_{cn} = ((3.47 - \log(Q_{rn}))^2 + (\log(F_r) + 1.22))^0.5$

Normalised pore pressure:

$u_p = \frac{\Delta u}{q_c - \sigma_{v0}}$

Normalised soil behaviour type (SBTn):

Calculated using Q_{rn} and F_r for the Robertson's 2010 normalised CPT soil behaviour chart using zone equations defined by P.W. Mayne in "Evaluating effective stress parameters and undrained shear strength of soft-firm clays from CPT and DMT" 2016

Undrained shear strength (s_u):

$s_u = \frac{q_c - \sigma_{v0}}{N_{kt}}$

Relative density (D_r):

$D_r = 100 \cdot \sqrt{\frac{Q_{rn}}{350}}$

Friction angle (ϕ'):

$\phi' = 17.60 + 11 \cdot \log(Q_{rn})$

Small strain shear modulus (G_0):

$G_0 = (q_c - \sigma_{v0}) \cdot (0.0188 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)})$

Estimated shear wave velocity (V_s):

$V_s = \sqrt{\frac{G_0}{\rho}}$ where $\rho = \frac{\gamma}{g}$

Constrained modulus (M):

$M = \alpha_{df}(q_c - \sigma_{v0})$

when $I_{cn} > 2.2$

$\alpha_{df} = Q_c$ when $Q_c < 14$

$\alpha_{df} = 14$ when $Q_c > 14$

when $I_{cn} < 2.2$

$\alpha_{df} = 0.0188 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)}$

Youngs modulus (E_s):


$E_s = (q_c - \sigma_{v0}) \cdot (0.015 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)})$

Estimated SPT N_{60} :

$N_{60} = \frac{q_c / P_a}{8.5 \cdot (1 - \frac{1}{10})}$

Zero Readings

kPa	Initial zeros	Final zeros	Final difference	Clean zeros	Clean difference
Cone resistance	6,349.60	6,356.90	7.31	-	-
Sleeve friction	451.90	444.20	-7.62	-	-
Pore pressure	705.10	705.80	0.73	-	-



General Information

Project: 14 Edmonton Road, Henderson, Auckland
Contractor: Ground Investigation
WGS84 (deg): -36.87760999999999, 174.635692
Elevation (m): Unknown
Date:
Location: 14 Edmonton Road, Henderson, Auckland
Rig details: 22 Tonne MAN Truck
Location method: Handheld GPS
Elevation datum:
Start time:

Test Setup

Standard: ISO 22476-1:2012

Test type:
Pre-Drill (m): 0.25
Start length (m): 0
Cone ID: 71238
Cone type: 15cm2 Subtraction

Cone class:
Manufacturer:
Calibration date:

Cone area ratio: 0.75
Sleeve area ratio: 0
Sleeve offset: 0.09
Filter type: U2 Stainless steel

Saturation method: Vacuum pump
Rig setup variation:

Test Result

Termination reason: Danger of buckling rods
Termination depth: 13.36
Ground water level: 1.8
Water level origin: Estimated

Backfill:
Observations and materials encountered:

Deviations and interruptions:
Deviations:
Interruptions:

Corrections applied:

Test category:

Operator name:

Manager name:

Corrected cone resistance:

$$R_c = q_c + u_2 \cdot (1 - \beta)$$
$$R_c = \frac{f_s}{q_c} \cdot 100$$

Friction ratio:

Non-normalised soil behaviour type (SBT):

Calculated using q_{un} and R_f for the Robertson's 2010 non-normalised CPT soil behaviour chart using zone equations defined by P.W. Mayne in "Evaluating effective stress parameters and undrained shear strength of soft-firm clays from CPT and DMT" 2016

Soil behaviour type index, (used for non-normalised SBT) :

$$I_c = \left((3.47 - \log(q_c))^2 + (\log(R_f) + 1.22) \right)^{0.5}$$

Friction ratio:

$$F_r = \frac{f_s}{q_c - \sigma_{v0}} \cdot 100$$

Refined normalised cone resistance:

$$Q_{rn} = \frac{(q_c - \sigma_{v0}) / \sigma_{v0}}{\left(\frac{\sigma_{v0}}{\sigma_{vm}} \right)^n}$$
 where $n = 0.381 \cdot I_c + 0.05 \cdot \left(\frac{\sigma_{v0}}{\sigma_{vm}} \right) - 0.05 \leq 1.0$

Normalised soil behaviour type index:

$$I_{cn} = \left((3.47 - \log(Q_{rn}))^2 + (\log(F_r) + 1.22) \right)^{0.5}$$

Normalised pore pressure:

$$B_p = \frac{\Delta U}{q_c - \sigma_{v0}}$$

Normalised soil behaviour type (SBTn):

Calculated using Q_{rn} and F_r for the Robertson's 2010 normalised CPT soil behaviour chart using zone equations defined by P.W. Mayne in "Evaluating effective stress parameters and undrained shear strength of soft-firm clays from CPT and DMT" 2016

Undrained shear strength (s_u):

$$s_u = \frac{q_c - \sigma_{v0}}{N_{sk}}$$

Relative density (D_r):

$$D_r = 100 \cdot \sqrt{\frac{Q_{rn}}{350}}$$

Friction angle (ϕ'):

$$\phi' = 17.60 + 11 \cdot \log(Q_{rn})$$

Small strain shear modulus (G_0):

$$G_0 = (q_c - \sigma_{v0}) \cdot (0.0188 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)})$$

Estimated shear wave velocity (V_s):

$$V_s = \sqrt{\frac{G_0}{\rho}}$$
 where $\rho = \frac{\gamma}{g}$

Constrained modulus (M):

$$M = \alpha_{df}(q_c - \sigma_{v0})$$

when $I_{cn} > 2.2$

$$\alpha_{df} = Q_c$$
 when $Q_c < 14$

$$\alpha_{df} = 14$$
 when $Q_c > 14$

when $I_{cn} < 2.2$

$$\alpha_{df} = 0.0188 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)}$$

Youngs modulus (E_s):

$$E_s = (q_c - \sigma_{v0}) \cdot (0.015 \cdot 10^{(0.55 \cdot I_{cn} + 1.68)})$$

Estimated SPT N_{60} :

$$N_{60} = \frac{q_c / P_a}{8.5 \cdot \left(1 - \frac{1}{10} \right)}$$

Zero Readings

kPa	Initial zeros	Final zeros	Final difference	Clean zeros	Clean difference
Cone resistance	6,870.60	6,821.70	-48.9	-	-
Sleeve friction	468.30	461.30	-7.01	-	-
Pore pressure	737.70	737.70	0	-	-

APPENDIX D


LOGS OF SHALLOW SITE INVESTIGATIONS



Drill Type: 50 mm Hand Auger
 Drilled By: DG
 Date Started: 21/8/18
 Date Finished: 21/8/18

Project No: 18511
 Coordinates:
 Ground Elevation:
 Water Level: 0.8m 21/08/2018

Logged By: DG
 Shear Vane No - Calibration Date: DR1768 - 21/12/2017
 Surface Conditions: Level, grass




HAND AUGER LOG WITH SCALA LOGS_18511-AH01-13 AUG-18.GPJ S+R_2013.GDT 13/2/23

Drill Type: 50 mm Hand Auger
Drilled By: NC
Date Started: 21/8/18
Date Finished: 21/8/18

Project No: 18511
Coordinates:
Ground Elevation:
Water Level: 2.6m 21/08/2018

Logged By: NC
Shear Vane No - Calibration Date: GEO122 - 1/12/2017
Surface Conditions: Near Level Asphalt




HAND AUGER LOG WITH SCALA LOGS_18511-AH01-13 AUG-18.GPJ S+R_2013.GDT 13/2/23

Drill Type: 50 mm Hand Auger
Drilled By: DG
Date Started: 21/8/18
Date Finished: 21/8/18

Project No: 18511
Coordinates:
Ground Elevation:
Water Level: Ground Water Not Encountered


Logged By: DG
Shear Vane No - Calibration Date: DR1768 - 21/12/2017
Surface Conditions: Slightly Sloping Grass



HAND AUGER LOG WITH SCALA LOGS_18511_AH01-13 AUG 18.GPJ S+R_2013.GDT 13/2/23

Drill Type: 50 mm Hand Auger
Drilled By: NC
Date Started: 21/8/18
Date Finished: 21/8/18

Project No: 18511
Coordinates:
Ground Elevation:
Water Level: Ground Water Not Encountered


Logged By: NC
Shear Vane No - Calibration Date: GEO122 - 1/12/2017
Surface Conditions: Near Level Asphalt


HAND AUGER LOG WITH SCALA LOGS_18511-AH01-13 AUG-18.GPJ S+R_2013.GDT 13/2/23

Drill Type: 50 mm Hand Auger
Drilled By: NC
Date Started: 21/8/18
Date Finished: 21/8/18

Project No: 18511
Coordinates:
Ground Elevation:
Water Level: 2.0m 21/08/2018

Logged By: NC
Shear Vane No - Calibration Date: GEO122 - 1/12/2017
Surface Conditions: Near Level Asphalt



HAND AUGER LOG WITH SCALA LOGS_18511_AH01-13 AUG 18.GPJ S+R_2013.GDT 13/2/23



SCALA PENETROMETER SHEET - TABLE OF BLOWS PER INCREMENT

JOB NAME: 14 Edmonton Road, Henderson JOB NO: 18511 TESTED BY: DEG/JL/NC DATE: 21/08/2018

Depth of Penetration [mm]	AH09	AH10	AH11	AH12	AH13						
DEPTH START[m] ➡	5.00	5.00	3.00	3.00	4.50						
50 mm	SUNK	SUNK	1	0.5	1						
100			2	0.5	2						
150		↓	2	11	1						
200		1	2	1	2						
250	↓	1	2	1	1						
300	1	1	3	1	2						
350	1	1	4	1	2						
400	2	2	5	1	2						
450	2	2	5	1	2						
500	1	2	5	1	4						
550	2	2	7	1	4						
600	2	2	6	1	5						
650	2	3	6	1	6						
700	2	1	10	2	5						
750	2	2	10	2	4						
800	2	3	10	2	4						
850	2	2	10	2	6						
900	2	2	10	2	6						
950	2	3		2	4						
1000	2	3		3	10						
1050	3	2		5	8						
1100	3	4		4	10						
1150	3	4		3	8						
1200	4	4		3	10						
1250	3	4		4	10						
1300	3	4		5	10						
1350	4	8		7	12						
1400	5	20+		8	12						
1450	4			8							
1500	4			10							
1550	6			10							
1600	7			10							
1650	10			10							
1700	11			10							
1750	14										
1800	20+										
1850											
1900											
1950											
2000											
DEPTH END [m] ➡	6.80	6.40	3.90	4.70	5.90						

Testing Method: NZS 4402:1988 Test 6.5.2 Dynamic Cone Penetrometer